

**PROVISIONAL TDS**

## HFS High Performance Fluorinated Solvent

HFS is a non-flammable, fluorinated solvent designed for use with Electrolube FPC, Fluorinated Polymer Coating. HFS is used to dilute FPC in order to maintain an in-use solids content of around 2%. HFS may also be suitable for general cleaning applications.

- Non-flammable solvent; reduces hazard for operators
- Used to dilute fluorinated coatings, such as Electrolube FPC
- Promotes cost effective and efficient application; very quick touch dry time
- Can be used as an electronic cleaning product and general degreasing applications

<b>Approvals</b>	<b>RoHS-2 Compliant (2011/65/EU):</b>	<b>Yes</b>
	<b>REACH Compliant:</b>	<b>Yes</b>

<b>Liquid Properties</b>	Appearance:	Colourless liquid
	Density @ 20°C:	1.44 g/ml
	Flash Point:	None
	Boiling Point:	45°C
	Evaporation Rate at 20°C:	<1 minute

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
<u>HFS Solvent</u>	5 Litre	HFS05L	48 Months

Revision 0: Sept 2015

**Copyright Electrolube 2013**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,  
Ashby de la Zouch,  
Leicestershire LE65 1JR  
T +44 (0)1530 419 600  
F +44 (0)1530 416 640  
BS EN ISO 9001:2008  
Certificate No. FM 32082