
Opening ELECTROSTATIC SHIELDING Length (L) STATSHIELD

Side Weld Seals 9.5mm (± 2.5mm) Tolerance W: ± 6mm / Tolerance L: ± 6mm





Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco Europe bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag. See TB-7057 - Requirements for Statshield ESD Bag Storage



Meets EN 61340-5-1 and Packaging standard IEC 61340-5-3 tested per IEC 61340-2-3 (ANSI/ESD STM11.11 and IEC 61340-4-8 (ANSI/ESD STM11.31)

Specifications:

Electrical Properties Typical Values Test Procedures/Method Surface Resistance: 1×10^4 to < 1×10^{11} ohms Outer Surface IEC 61340-2-3 1×10^4 to $< 1 \times 10^{11}$ ohms Inner Surface IEC 61340-2-3 Discharge Shielding <20 n.J IFC 61340-4-8 Charge Generation Teflon: 0.09 nC/sq. in. Modified Incline Plane Quartz: 0.01 nC/sq. in. Modified Incline Plane Capacitance Probe (to dissipate 1 KV) <30 volts EIA 541

Physical Properties

Date & Lot Code

Printed for QC

Traceablility

Film Thickness 3.0 Mils ± 10% MIL-STD-3010, 1003 **Light Transmission** >40% (Tobias) ASTM D-1003 Heat Seal >10 lbs/in 375°F, 1/2 sec 60 psi Tensile Strength 4600 PSI, 32 MPa **ASTM 882** Puncture Resistance MIL-STD-3010, 2065 >10 lbs Marking Adhesion Pass IPC-TM-650 2.4.1 Cleanliness Silicone not detected ASTM E 168

Chemical Properties

Corrosion No effect on aluminium, copper, silver, Sn-Pb coated foil, stainless steel. low carbon steel

Polycarbonate Capability,

Bag is free of amines, N-octanoic acid, silicones and heavy metals.

Per Packaging Standard EN 61340-5-3 clause 5.3 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides both:

- dissipative or conductive materials for intimate contact
- a structure that provides electrostatic discharge shielding."

RoHS 2. REACH and Conflict Minerals Statement

None of the RoHS 2 restricted materials, or REACH substances of very high concern as of 2015/12/17, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Directive 2011/65/EC Article 4.1. and Regulation (EC) No. 1907/2006/CE. See Desco Europe Limited Warranty at DescoEurope.com.

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc.



Specifications and procedures subject to change without notice.

DESCO EUROPE

Statshield® Bag, Shielding, Metal-In Construction

DESCO EUROPE 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY. HERTFORDSHIRE, SG6 1BE, UK PHONE: +44 (0) 1462 672005

E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number 201000

DATE: July 2017