



- A. This Desco Europe PCB rack is moulded of a static dissipative thermoplastic compound based on polypropylene copolymer with carbon black, and reinforced with mica flake.
- B. These racks are designed to protect CMOS loaded boards in storage.
- C. Recommended maximum operating temperature is 135°C.
- D. Open carrying handles.
- E. Measurements: 140mm x 465mm.
- F. Weight: 0.4kg.
- G. 25 slots measure 3mm x 7.5mm on a 15.6mm pitch.

"Tools intended for use within the EPA [ESD protected area] shall, as far as is practicable, be so constructed that they do not generate or hold an electrostatic chargeAll tools and machinery, for example electrical, mechanical or pneumatic, shall be so constructed that any non-insulating part of the tool or machine which may touch an ESDS [ESD sensitive items] shall be at EPA ground potential."
 [EN 61340-5-1 clause 5.2.10 Tools, machinery, dispensers and test equipment]



Properties		Unit	Test Method
Electrical Properties			
Surface Resistance	1 x 10 ⁵ to 1 x 10 ⁸	Ohms/square	ASTM D-257
Volume Resistance	1 x 10 ⁴ to 1 x 10 ⁷	Ohms-cm	ASTM D-257
Mechanical Properties			
Tensile Strength @ Break	3600 (25)	psi (MPa)	ASTM D-638
Tensile Elongation @ Break	6-9	%	ASTM D-638

ITEM	DESCRIPTION
237225	Conductive PCB Rack, 140mm x 465mm, High Temperature



Made in the United States of America

Unless otherwise noted, tolerance ±10%
 Specifications and procedures subject to change without notice.

Conductive PCB Rack, 140mm x 465mm, High Temperature

DESCO EUROPE

DESCO EUROPE
 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
 HERTFORDSHIRE, SG6 1BE, UK
 PHONE: +44 (0) 1462 672005
 E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
237225

DATE:
 December
 2017