




Made in the United States of America



SPECIFICATIONS

- Ideal for working on heavier assemblies in an EPA
- ESD protective for use with ESD sensitive assemblies
- Durable 1/4" (6mm) thick Dissipative, Crosslink Polyethylene Foam
- Galvanized Steel Turntable located at the bottom
- Size: Choice of 12-1/2" (318mm) or 15-1/2" (394mm) Octagon (across flats)
- Very low profile - both sizes only 1" (25mm) high
- Weight capacity 50 lbs (23 Kg)
- Volume Resistance 1×10^6 to $< 1 \times 10^9$ ohms per ANSI/STM11.12
- Meets worksurface require limit of ANSI/ESD S20.20 per ANSI/ESD S541 and ESD TR53
- Electrostatic charges removed to ground via contact on grounded ESD worksurface or via ground cord from ring terminal
- Made in the United States of America



47200 in use
([47204](#) Ground cord sold separately)



47201 in use

Item	Size (Octagon across flats)
47200	12-1/2" (318mm)
47201	15-1/2" (394mm)



Galvanized Steel Turntable

Unless specified tolerance is $\pm 10\%$

Specifications and procedures subject to change without notice.

ESD DISSIPATIVE TURNTABLE

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
47200

DATE
June
2016

PROTEKTIVE PAK