

CCL Non-Flammable Contact Cleaner

CCL is a very fast evaporating solvent cleaner developed for use on live electrical equipment to clean switches and contacts. It is 100% Ozone Friendly, non-flammable and evaporates quickly, leaving no residue. The low surface tension means that it has exceptional penetrating power.

- Very fast evaporation time; efficient cleaning of electrical contacts
- Loosens and removes accumulated deposits of dirt grease and oxides
- Low hazard product; low toxicity and non-flammable
- Safe with most plastics and rubbers; ideal for a variety of substrates

Approvals	RoHS-2 Compliant (2011/65/EU):	Yes
Typical Properties	Boiling Point (°C)	43
	Flash Point (°C)	None
	Density @ 20°C (g/ml)	1.49
	Vapour Pressure (mmHg)	298
	Solubility in Water	Sparingly Soluble
	Residue on Evaporation	None
	Relative Evaporation Rate	<1 (Butyl Acetate = 1)

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
<u>CCL Aerosol</u>	200ml Aerosol with Brush	CCL200DB	24 Months

Directions for Use

CCL is designed for use as a cleaner for electrical contacts and switches to ensure low contact resistance. The product is compatible with most plastics and as it is non-flammable, it can be used on live equipment where flammable solvents are prohibited.

Spray directly onto the contacts and switches to be cleaned. The power of the jet will clean the contacts, leaving no residues. Buds or cloths may also be used if desired.

Revision 1: Mar 2014

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,
Ashby de la Zouch,
Leicestershire LE65 1JR
T +44 (0)1530 419 600
F +44 (0)1530 416 640
BS EN ISO 9001:2008
Certificate No. FM 32082